

EJ-OR4-15U35 ▶ Open Rack



DETAIL

- Overall Width: base to base = 22 1/8", post to post = 20 1/8"
- Overall Depth: base to base = 35.5", post to post = 28.5"
- Overall Height: 30.75"
- Hole to hole width: 19", Maximum equipment' width: 17 11/16"
- Useable height: 26.25"
- For slide rail: brackets length must be less than 22.5"

Specifications

Standard

- 2 of welded main frames
- 2 heavy duty plinth (bases)
- 4 piece triangle brackets
- 2 sets of depth supporter
- 50 pcs M6 bolt screws W/washer
- 50 pcs M5 self-tapping screws
- 50 pcs M6 cage nuts
- tools and installation manual

Feature

- 4 pieces heavy duty triangle brackets on bottom of rack to make sure the main frame and plith were fully connected and even support much better strength
- Additional depth supporter on the top of rack to ensure main frames are fully connected
- Allows you to install heavy duty server, not just for cabling
- Allows you to install the sliding rail, not just stack them or center mounted
- Allows you to install the wheel or bolt on the ground which you prefered
- Allows you to connecting more racks side by side
- Easy assembly
- Shipping within 2 days

EJ-OR4-20U35 ▶ Open Rack



Specifications



- 2 of welded main frames
- 2 heavy duty plinth (bases)
- 4 piece triangle brackets
- 2 sets of depth supporter
- 50 pcs M6 bolt screws W/washer
- 50 pcs M5 self-tapping screws
- 50 pcs M6 cage nuts
- tools and installation manual

Feature

- 4 pieces heavy duty triangle brackets on bottom of rack to make sure the main frame and plith were fully connected and even support much better strength
- Additional depth supporter on the top of rack to ensure main frames are fully connected
- Allows you to install heavy duty server, not just for cabling
- Allows you to install the sliding rail, not just stack them or center mounted
- Allows you to install the wheel or bolt on the ground which you prefered
- Allows you to connecting more racks side by side
- Easy assembly
- Shipping within 2 days



DETAIL

- Overall Width: base to base = 22 1/8", post to post = 20 1/8"
- Overall Depth: base to base = 35.5", post to post = 28.5"
- Overall Height: 39.5"
- Hole to hole width: 19", Maximum equipment' width: 17 11/16"
- Useable height: 35"
- For slide rail: brackets length must be less than 22.5"