



**AC Input:**

- > Input Voltage-38~72V DC
- > Input Current 250w 10A max
- > Input Frequency 47/63 Hz
- > Inrush Current 30A max at nominal line 25°C cold start
- > Efficiency >65% @ full load ,nominal line
- > Leakage Current 3.5mA max.

**DC Output:**

Output	Voltage	Regulation	Min .Load	Max .Load	Ripple
V1	+5V	±5%	0.5A	30A	50mV
V2	+12V	±5%	0.3A	14A	120mV
V3	+3.3V	±5%	0.5A	22A	50mV
V4	-5V	±10%	0A	0.5A/NA	120MV
V5	-12	±10%	0A	0.5A/1A	120mV
V6	+5VSB	±5%	0A	3A	50mV

**Features...**

- > 250W 6 Output, Dadd 0.1uF and 10uF capacitors across output
- > IEC-60950 CLASS B
- > Operating temperature range from 0°C to 50°C
- > Build in DC remote ON/OFF , PG/PF TTL signal
- > Build in long life ball bearing fan
- > Build in thermal fan speed control
- > Compiles with FCC Class B,CISPR Pub:22 Class B  
EN60950 Class B, and CE requirements
- > UL/cUL 60950, TUV and CB EN 60950 certified
- > MTBF 100KHRs @ 25°C per MIL- HDBK-217F
- > 2 years manufacturer warranty