



ever Joy ever Triumph

Worldwide

Product



■ EJ-KVM408J31

Features

- 8/16 port Two-Console PS/2 KVM switch is 19" rack mount size design.
- Support one CAT5 remote console up to 500 feet away from KVM switch.
- Support Microsoft Intellimouse, Microsoft Intellimouse Explorer, Logitech Net Mouse or the other fully compatible MS mice.
- Support DOS, Win3.X, Win95/98/98SE/2000/ME/XP, WinNT, Netware, Unix, Linux
- Support iMAC, Power MAC and Sun Microsystems with USB port (Need work with USB-PS/2 adapter)
- Hot Plug - Add PCs or Remove Connected PCs for Maintenance without Powering Down the KVM switch or PCs.
- Very High Video Quality - Up To 1920X1440, Bandwidth: 200MHz
- No Software Required - easy PC selection via On Screen Display Manual, Push Buttons, Hot Keys
- Support eight characters password protection and search PC server name
- Auto Scan Mode for monitoring PCs and flexible Scan time from 5~99 seconds
- Keyboard status restored when switching PCs
- LED Display for easy status monitoring
- Buzzer sound for switching port confirmation.
- No DIP switch setting needed and auto detect daisy chain bank



ever Joy ever Triumph

Worldwide

Product

■ EJ-KVM408J31

Technical Specifications

Model No.	Two-console 8 port PS/2 KVM Switch	Two-console 16 port PS/2 KVM Switch
PC Port	8	16
Console Port	2 (One Local and CAT5)	2 (One Local and CAT5)
Remote Console Port Receiver	1	1
PC Port Connector (All Female Types)	VGA HDDB 15pin (shared with PS/2 keyboard and Mouse)	
Console Port Connector (All Female Types)	Local Console: PS/2 Keyboard Mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15pin Remote Console: RJ-45 8P8C	
Daisy Chain Port Connector (All Female Type)	PS/2 Keyboard mini Din 6 pin PS/2 Mouse Mini Din 6 pin VGA HDDB 15pin	
PC selection	On Screen Display Menu, Hot Key, Push Button	
PC Port LED	8	16
Bank 7 segment LED	1	
On Screen Display Control	Yes	
Scan Intervals	5~99 Sec.	
Keyboard Emulation	PS/2	
Mouse Emulation	PS/2	
VGA Resolution	1920X1440	
Bandwidth	200MHz	
Daisy Chain MAX Level	8 levels	
MAX PC Connection	120	128
Housing	Metal	
KVM Switch Power Adapter	DC 9V, 500mA	
Cat5 Remote Console Receiver Power Adapter	DC 9V, 500mA	
Operation Temperature	0~50°C	
Storage Temperature	-20 ~ 60°C	
Humidity	0~95%, Non-Condensing	
Size	19" Rack Mount / 1RU	19" Rack Mount / 1RU
Weight (g)	2010	2220
Dimension (cm)	41(L) X 16.5(W) X 4.4(H)	41(L) X 16.5(W) X 4.4(H)