

EJ-RC11U-S8

▶ 19" CLM Server Cabinet



Specifications

Material

Cabinet frame of extrude aluminum sections front and clear door, side panels, top, bottom plates and plinth of sheet metal

Standard

- · Die-cast heavy duty aluminum post frame
- · Plexiglass front door W/lock
- · Heavy duty sheet metal side and rear doors W/lock
- Top and bottom panels W/cable access hole
- · Full size mounting strips front and rear
- 3 of 12cm fans (115CFM each) on top
- · 4 heavy duty wheels
- · 4 leveling feet
- 50 pcs M6 bolt screws W/washer
- · Grounding wires

Feature

- · Good air ventilation
- You could increase to total 8 fans
- · All doors design with the spring latch, easy remove, tool less
- · Water or dust resist from top
- Easy assemble
- · Shipping within 2 days
- Available in white and black color, or any colors you prefer

Detail

2168 Series Cabinet:

- Overall:
- Width: 23.6"
- depth: 31.5"
- Height: 30"

Interior:

- Width: Hole to Hole (center) = 19" (18.25")
- Entrance (right rail to left rail): 17 5/8"
- Depth of front railing to rear door: Self-tapping type = 28.25" Square
 - type = 28.75"
- Useable height: 19.75"
- Max. length of sliding rail's brackets: Self-tapping type = 23.75"

Square type = 25 5/8"