

EJ-RC29U-S8

► 19" CLM Server Cabinet



Specifications

Material

Cabinet frame of extrude aluminum sections front and clear door, side panels, top, bottom plates and plinth of sheet metal

Standard

- Die-cast heavy duty aluminum post frame
- Plexiglass front door W/lock
- Heavy duty sheet metal side and rear doors W/lock
- Top and bottom panels W/cable access hole
- Full size mounting strips front and rear
- 3 of 12cm fans (115CFM each) on top
- 4 heavy duty wheels
- 4 leveling feet
- 50 pcs M6 bolt screws W/washer
- Grounding wires

Feature

- Good air ventilation
- You could increase to total 8 fans
- All doors design with the spring latch, easy remove, tool less
- Water or dust resist from top
- Easy assemble
- Shipping within 2 days
- Available in white and black color, or any colors you prefer

Detail

2168 Series Cabinet:

Overall:

* Width: 23.6"

* depth: 31.5"

* Height: 61"

Interior:

* Width: Hole to Hole (center) = 19" (18.25")

* Entrance (right rail to left rail): 17 5/8"

* Depth of front railing to rear door: Self-tapping type = 28.25"
Square type = 28.75"

* Useable height: 51"

* Max. length of sliding rail's brackets: Self-tapping type = 23.75"
Square type = 25 5/8"